

CARACTERISTICAS DE TUBERÍA DE CONCRETO CON JUNTA HERMETICA

ESPECIFICACIONES NMX C 401 Y NMX C 402 GRADO 1

DIAMETRO		LONGITUD UTIL (m)	ESPESOR DE PARED		PESO			
plg.	cm.		plg.	cm.	lb/pza	lb/m	kg/pza	kg/m
6	15,20	1,25	1,06	2,70	101	81	46	37
8	20,30	1,25	1,14	2,90	172	137	78	62
12	30,50	2,44	2,00	5,10	903	370	410	168
15	38,10	2,44	2,41	6,10	1.179	483	535	219
18	45,70	2,44	2,50	6,40	1.410	578	640	262
24	61,00	2,44	3,00	7,60	2.115	867	960	393
30	76,20	2,44	3,50	8,90	2.820	1.156	1.280	525
36	91,40	2,44	4,00	10,20	3.966	1.625	1.800	738
42	106,70	2,44	4,50	11,40	5.123	2.099	2.325	953
48	121,90	2,44	5,00	12,70	6.610	2.709	3.000	1.230
60	152,40	2,44	6,06	15,40	9.849	4.036	4.470	1.832
72	182,90	2,44	6,50	16,50	13.738	5.630	6.235	2.555



TUBOS ECOLOGICOS DE CONCRETO S.A. DE C.V.

Km. 15 Carretera Federal Puebla - Tehuacan Tel. 286-15-36 286-15-37

WWW.TUBECO.COM.MX